

County Surveyor's Record, Douglas County, Oregon

42
Subdivisions of T. 24 S., R. 2 W.

CHAINS	
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.20	Intersect N. and S. line 30 lks. N. of the cor. to secs. 11, 12, 13 and 14. Thence I run S.89*56'W. on a true line bet. secs. 11 and 14, Var. 20*E. Through heavy timber and dense brush. Ascend about 200 ft. to
16.00	Top of spur, course SE. and descend about 350 ft.
40.10	Set a basalt stone 12x9x9 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. corner marked $\frac{1}{4}$ on N. face, from which A fir, 30 ins. diam., bears S.52*E. 45 lks. dist. marked $\frac{1}{4}$ S B T. A chinquapin, 6 ins. diam., bears N.28*E. 28 lks. dist. marked $\frac{1}{4}$ S B T.
54.25	Creek, 1 lk. wide, course Sw. and ascend about 150 ft. to
67.50	Spur, course S. and descend about 200 ft. to
80.20	The cor. to secs. 10, 11, 14 and 15. Land, mountainous and heavily timbered, fir and hemlock, with dense undergrowth of vine maple, 80.20 chs. Soil, sandy and rocky, 3rd and 4th rate. Sept. 13, 1894.
	N.0*2'W. bet. secs. 10 and 11. Var. 20*E. Through heavy timber. Ascend about 75 ft. to
5.00	Top of spur, course SW. and descend about 50 ft. to
8.75	Bottom of ravine, course SW. and ascend about 100 ft. to
16.75	Top of spur, course SW. and descend about 250 ft. to
34.50	Creek, 5 lks. wide, course W. and ascend about 250 ft.
40.00	Set a post 3 ft. long and 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on W. face, from which A yew, 6 ins. diam., bears S.85*E. 33 lks. dist.