

County Surveyor's Record, Douglas County, Oregon

45
Subdivisions of T. 24 S., R. 2 W.

CHAINS	Dense undergrowth of rhododendron and vine maple, 79.70 chs. Soil, sandy and rocky, 3rd and 4th rate.
	From the cor. to secs. 3, 4, 33 and 34 on the South boundary of the township, which is a post, 4 ft. long and 4 ins. sq., firmly set in the ground, marked T 24 S S 34 on NE., R 2 W S 3 on SE., T 25 S S 4 on SW. and S 33 on NW. faces, with 3 notches on E. and W. edges, from which
	A fir, 20 ins. diam., bears N.19*E. 72 lks. dist. marked T 24 S R 2 W S 34 B T.
	A hemlock, 30 ins. diam., bears S.43*E. 22 lks. dist. marked T 25 S R 2 W S 3 B T.
	A fir, 18 ins. diam., bears S.43*W. 22 lks. dist. marked T 25 S R 2 W S 4 B T.
	A fir, 30 ins. diam., bears N.20*W. 18 lks. dist. marked T 24 S R 2 W S 33 B T.
	I run N.0*2'W. bet. secs. 33 and 34
	Var. 19*30'E.
	Through heavy timber, ascend about 100 ft. to
5.00	Top of spur, course SE. and descend about 250 ft. to
29.00	Creek, 1 lk. wide, course SE. and ascend about 250 ft.
40.00	Set a basalt stone 16x12x10, ^{I/V5,} 11 ins. in the ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face, from which
	A fir, 12 ins. diam., bears S.35*E. 25 lks. dist. marked $\frac{1}{4}$ S B T.
	A fir, 15 ins. diam., bears N.75*W. 11 lks. dist. marked $\frac{1}{4}$ S B T.
55.00	Top of spur, course SE. and descend about 200 ft. to
64.40	Creek, 2 lks. wide, course NE. and ascend about 75 ft. to
70.00	Top of spur, course E. and descend about 75 ft. to
80.00	Set a basalt stone 15x12x10 ins., 10 ins. in the ground for the cor. to secs. 27, 28, 33 and 34, marked with