

County Surveyor's Record, Douglas County, Oregon

47

Subdivisions of T. 24 S., R. 2 W.

CHAINS	
60.90	Creek, 7 lks. wide, course S. and ascend about 100 ft. to
68.00	Top of spur, course S. and descend about 100 ft. to
72.50	Creek, 8 lks. wide, course SE. and ascend about 200 ft. to
80.24	The cor. to secs. 27, 28, 33 and 34. Land, mountainous and heavily timbered with fir and hemlock, with dense undergrowth of the same, 80.24 chs. Soil, sandy and rocky, 3rd and 4th rate.
	N.89*48'W. on a random line bet. secs. 28 and 33. Var. 20*E.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.56	Intersect N. and S. line 48 lks. N. of the cor. to secs. 28, 29, 32 and 33, which is a post 4 ft. long and 4 ins. sq., firmly set in the ground, marked T 24 S S 28 on NE., R 2 W S 33 on SE., S 34 on SW. and S 29 on NW. faces, with 1 notch on S. and 4 notches on E. edges from which A fir, ins. diam., bears N.70*E. 20 lks. dist. marked T 24 S R 2 W S 28 B T. A fir, 8 ins. diam., bears S.20*E. 10 lks. dist. marked T 24 S R 2 W S 33 B T. A fir, ins. diam., bears S.60*W. 18 lks. dist. marked T 24 S R 2 W S 34 B T. A fir, 10 ins. diam., bears N.15*W. 22 lks. dist. marked T 24 S R 2 W S 29 B T. Thence I run N.89*51'E. on a true line bet. secs. 28 and 33. Var. 21*E.
20.00	Through heavy timber and ascend about 200 ft. to Top of ridge, course SE. and descend about 400 ft.
39.56	Set a basalt stone 16x9x6, ^{and} 11 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which A hemlock, 6 ins. diam., bears S.74*W. 28 lks. dist. marked $\frac{1}{4}$ S B T. A fir, 36 ins. diam., bears N.70*W. 58 lks. dist.