

County Surveyor's Record, Douglas County, Oregon

52
Subdivisions of T. 24 S., R. 2 W.

CHAINS	
	Thence I run
	S.89*42'W. on a true line bet. secs. 15 and 22.
	Var. 20*E.
	Through heavy timber, ascend about 40 ft. to
3.00	Top of spur, course SE. and descend about 100 ft. to
10.00	Creek, 25 lks. wide, course SE. and ascend about 400 ft.
40.20	Set a post, 3 ft. long and 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, from which
	A vine maple, 6 ins. diam., bears N.5*E. 36 lks. dist. marked $\frac{1}{4}$ S B T.
	A vine maple, 6 ins. diam., bears S.82*E. 11 lks. dist. marked $\frac{1}{4}$ S B T.
60.20	Top of spur, course SE. and descend about 25 ft. to
61.25	Creek, 2 lks. wide, course SE. and ascend about 200 ft. to
75.40	Top of spur, course SE. and descend about 60 ft. to
79.40	Bottom ravine, course SE. and ascend about 50 ft. to
80.40	The cor. to secs. 15, 16, 21 and 22.
	Land, mountainous and heavily timbered with fir and hem- lock, with dense undergrowth of vine maple and hemlock, 80.40 chs.
	Soil, sandy and rocky, 3rd and 4th rate.
	Sept. 17, 1894.
<hr/>	
	N.0*2'W. bet secs. 15 and 16.
	Var. 20*E.
	Through heavy timber, ascend about 350 ft. to
23.50	Top of spur, course E. and descend about 500 ft.
40.00	Set a post 3 ft. long and 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on W. face, from which
	A fir, 60 ins. diam., bears N.10*E. 22 lks. dist. marked $\frac{1}{4}$ S B T.
	A hemlock, 24 ins. diam., bears N.13*W. 40 lks. dist. marked $\frac{1}{4}$ S B T.
59.75	Creek, 10 lks. wide, course E. and ascend about 50 ft. to