

53

Subdivisions of T. 24 S., R. 2 W.

CHAINS	
61.25	Top of spur, course E. and descend about 50 ft. to
63.25	Creek, 10 lks. wide, course SE. and ascend about 300 ft.
	to
80.00	Set a post 4 ft. long and 4 ins. sq., 24 ins. in the ground for cor. to secs. 9, 10, 15 and 16, marked T 24 S S 10 on NE., R 2 W S 15 on SE., S 16 on SW. and S 9 on NW. faces, with 4 notches on S. and 3 notches on E. edges, from which
	A hemlock, 30 ins. diam., bears N.35*E. 113 lks. dist. marked T 24 S R 2 W S 10 B T.
	A vine maple, 6 ins. diam., bears S.69*E. 52 lks. dist. marked T 24 S R 2 W S 15 B T.
	A cedar, 24 ins. diam., bears S.55*W. 52 lks. dist. marked T 24 S R 2 W S 16 B T.
	A yew, 9 ins. diam., bears N.10*W. 52 lks. dist. marked T 24 S R 2 W S 9 B T.
	Land, mountainous and heavily timbered with fir and hemlock, with dense undergrowth of vine maple and rhododendron, 80.00 chs.
	Soil, sandy and rocky, 3rd and 4th rate.
	N.89*42'E. on a random line bet. secs. 10 and 15. Var. 20*E.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.48	Intersect N. and S. line at the cor. to secs. 10, 11, 14 and 15.
	Thence I run
	S.89*42'W. on a true line bet. secs. 10 and 15. Var. 20*E.
3.00	Through heavy timber, ascend about 75 ft. to
32.50	Top of spur, course SW. and descend about 400 ft. to
40.24	Creek, 20 lks. wide, course S. and ascend about 600 ft.
	Set a basalt stone 12x10x6 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, from which
	A hemlock, 20 ins. diam., bears S.7*W. 33 lks. dist.