

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 2 W.

CHAINS	<p>marked $\frac{1}{4}$ S B T.</p> <p>A hemlock, 14 ins. diam., bears N.12*W. 35 lks. dist.</p> <p>marked $\frac{1}{4}$ S B T.</p>
70.00	Top of spur, course SE. and descend about 100 ft. to
80.48	The cor. to secs. 9, 10, 15 and 16.
	Land, mountainous and heavily timbered with fir and hemlock, with dense undergrowth of rhododendron, 80.48 chs.
	Soil, sandy and rocky, 3rd and 4th rate.
	Sept. 18, 1894.
	N.0*2'W. bet. secs. 9 and 10.
	Var. 20*E.
	Through heavy timber, ascend about 200 ft. to
20.00	Top of ridge, course NW. & SE. and descend about 200 ft. to
38.25	Creek, 1 lk. wide, course NE. and ascend about 250 ft.
40.00	Set a basalt stone 15x12x6 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which
	A dogwood, 8 ins. diam., bears N.85*W. 35 lks. dist. marked $\frac{1}{4}$ S B T.
	A fir, 18 ins. diam., bears N.33*30'E. 81 lks. dist. marked $\frac{1}{4}$ S B T.
63.00	Top of ridge, course NW. & SE. and descend about 150 ft. to
80.00	Set a post, 4 ft. long and 4 ins. sq., 24 ins. in the ground for cor. to secs. 3, 4, 9 and 10, marked T 24 S S 3 on NE., R 2 W S 10 on SE., S 9 on SW. and S 4 on NW. faces, with 5 notches on S. and 3 notches on E. edges, from which
	A fir, 18 ins. diam., bears N.27*30'E. 50 lks. dist. marked T 24 S R 2 W S 3 B T.
	A fir, 30 ins. diam., bears S.46*30'E. 18 lks. dist. marked T 24 S R 2 W S 10 B T.
	A hemlock, 30 ins. diam., bears S.33*W. 28 lks. dist. marked T 24 S R 2 W S 9 B T.