

## County Surveyor's Record, Douglas County, Oregon

50

## Subdivisions of T. 24 S., R. 2 W.

CHAINS	
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.15	Intersect the north boundary of the township 45 lks. W. of the cor. to secs. 3, 4, 33 and 34. Thence I run S.0*3'W. on a true line bet. secs. 3 and 4. Var. 20*E. Through heavy timber, ascend about 200 ft.
9.00	Creek, 1 lk. wide, course NE.
24.00	Top of ridge, course SE. and descend about 300 ft.
40.15	Set a post 3 ft. long and 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on W. face, from which A hemlock, 18 ins. diam., bears S.39*W. 45 lks. dist. marked $\frac{1}{4}$ S B T. A hemlock, 7 ins. diam., bears S.50*E. 8 lks. dist. marked $\frac{1}{4}$ S B T.
47.00	Creek, 2 lks. wide, course NE. and ascend about 50 ft.
50.50	Top of spur, course SE. and descend about 100 ft. to
60.00	Creek, 2 lks. wide, course NE. and ascend about 40 ft. to
63.00	Top of ridge, NW. and SE. and descend about 150 ft. to
79.90	Creek, 5 lks. wide, course NE. and ascend about 100 ft. to
80.15	The cor. to secs. 3, 4, 9 and 10. Land, mountainous and heavily timbered with fir and hem- lock, with dense undergrowth of vine maple and rhodo- dendron, 80.15 chs. Soil, sandy and rocky, 3rd and 4th rate. Sept. 19, 1894.
	From the cor. to secs. 20, 21, 28 & 29 I run N.0*3'W. bet. secs. 20 and 21. Var. 20*E. Through heavy timber. Descend about 10 ft. to