

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 2 W.

CHAINS 33.50	Bottom of ravine, course SE. and ascend about 200 ft.
40.10	Set a post 3 ft. long and 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S. on N. face, from which A vine maple, 4 ins. diam., bears N.50*W. 22 lks. dist., marked $\frac{1}{4}$ S B T. A vine maple, 4 ins. diam., bears S.20*E. 14 lks. dist., marked $\frac{1}{4}$ S B T.
46.00	Top of ridge, course N. & S. and descend about 200 ft. to
80.20	The cor. to secs. 16, 17, 20 and 21. Land, mountainous and heavily timbered with fir and hemlock, with dense undergrowth of vine maple, rhododendron and hemlock, 80.20 chs. Soil, sandy and rocky, 3rd and 4th rate. Sept. 20, 1894.
	S.89*47'W. on random line bet. secs. 17 and 20. Var. 19*E.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.50	Intersect the N. and S. line 50 lks. S. of the cor. to secs. 17, 18, 19 and 20 which is a post 4 ft. long and 4 ins. sq., firmly set in the ground, marked T 24 S S 17 on NE., R 2 W S 20 on SE., S19 on SW. and S 18 on NW. faces with 3 notches on S. and 5 notches on E. edges, from which A fir, 12 ins. diam., bears N.50*E. 17 lks. dist. marked T 24 S R 2 W S 17 B T. A fir, 10 ins. diam., bears S.40*E. 35 lks. dist. marked T 24 S R 2 W S 20 B T. A fir, 18 ins. diam., bears S.35*W. 55 lks. dist. marked T 24 S R 2 W S 19 B T. A fir, 36 ins. diam., bears N.5*W. 15 lks. dist. marked T 24 S R 2 W S 18 B T. Thence I run S.89*52'E. on a true line bet. secs. 17 and 20. Var. 20*E.