

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 2 W.

CHAINS	Through heavy timber, ascend about 100 ft. to
5.00	Top of spur, course SE. and descend about 30 ft. to
7.00	Creek, 2 lks. wide, course SE.
10.25	Creek, 2 lks. wide, course SE. and ascend about 300 ft.
39.50	Set a basalt stone 15x12x6 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N. face, from which A fir, 36 ins. diam., bears N.20*W. 11 lks. dist. marked $\frac{1}{4}$ S B T. A fir, 30 ins. diam., bears S.50*W. 11 lks. dist. marked $\frac{1}{4}$ S B T.
43.00	Top of ridge, course NW. & SE. and descend about 100 ft.
50.00	Bottom of ravine, course S. and ascend about 60 ft. to
60.00	Top of spur, course S. and descend about 100 ft. to
67.20	Creek, 2 lks. wide, course SE. and ascend about 150 ft. to
79.50	The cor. to secs. 16, 17, 20 and 21. Land, mountainous, and heavily timbered with fir and hemlock. Dense undergrowth of the same, 79.50 chs. Soil, sandy and rocky, 3rd and 4th rate.
	N.0*3'W. bet. secs. 16 and 17. Var. 19*E.
	Through heavy timber, ascend about 300 ft. to
25.00	Top of ridge, course NE. & SW. and descend about 400 ft.
40.00	Marked a stone in place 12x12x6 ins. above ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, with a cross(x) at the exact cor. point, from which A hemlock, 18 ins. diam., bears N.60*E. 47 lks. dist. marked $\frac{1}{4}$ S B T. A fir, 36 ins. diam., bears S.33*W. 66 lks. dist. marked $\frac{1}{4}$ S B T.
55.00	Creek, 8 lks. wide, course W. and ascend about 300 ft.
56.25	Creek, 1 lk. wide, course SW.
80.00	Set a post 4 ft. long and 4 ins. sq., 24 ins. in the ground for cor. to secs. 8, 9, 16 and 17, marked T 24