

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 2 W.

CHAINS	
19.50	Creek, 4 lks. wide, course NW. in a rocky canyon, 80 lks. wide, with perpendicular rocky walls on each side about 50 ft. high and ascend about 200 ft. to
29.00	Top of ridge, course NW. and descend about 150 ft. to
36.00	Bottom ravine, course NW. and ascend about 300 ft.
39.80	Set a basalt stone 12x12x6 ins. in the ground, marked $\frac{1}{4}$ on N. face, from which A hemlock, 14 ins. diam., bears N.78*30'E. 27 lks. dist., marked $\frac{1}{4}$ S B T. A hemlock, 18 ins. diam., bears S.30*E. 29 lks. dist. marked $\frac{1}{4}$ S B T.
50.00	Top of ridge, course NW. & SE. and descend about 150 ft. to
76.00	Bench, course N. & S. Thence over bench.
79.28	Fir, 30 ins. diam.
79.60	The cor. to secs. 5, 6, 7 and 8. Land, mountainous and heavily timbered with fir and hemlock. With a dense undergrowth of vine maple, and rhododendron, 79.60 chs. Soil, sandy and rocky, 3rd and 4th rate.
	West, on a random line bet. secs. 6 and 7. Var. 20*E.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.40	Intersect the west boundary of the Tp. 20 lks. N. of the cor. to secs. 1, 6, 7 and 12, which is a post 4 ft. long and 4 ins. sq., firmly set in the ground, marked T 24 S S 6 on NE., R 2 W S 7 on SE., R 3 W S 12 on SW. and S 1 on NW. faces, with 1 notch on N. and 5 notches on S. edges, from which A maple, 7 ins. diam., bears N.71*E. 20 lks. dist. marked T 24 S R 2 W S 6 B T. A yew, 12 ins. diam., bears S.55*E. 70 lks. dist. marked T 24 S R 2 W S 7 B T.