

73

Retracements of the East Boundary of T. 24 S., R. 2 W.
as surveyed by Carl S. Nicklin, Deputy Surveyor, under contract
No. 664, dated May 23, 1896.

CHAINS

Preliminary to the survey of the subdivisional lines of
T. 24 S., R. 1 W., from the cor. of Tps. 24 and 25 S.,
R. 2 W., which I re-established on the W. bdy. of T.
24 S., R. 1 W., July 18, 1896, I run
North, on a blank line, bet. secs. 31 and 36.

36.88

To a point, 39 lks. E. of $\frac{1}{4}$ sec. cor. This $\frac{1}{4}$ sec. cor. I
find in a delapidated condition; B. T. in sec. 31
blown down; no trace of post to be found. I re-estab-
lish as follows: At the exact point for the $\frac{1}{4}$ sec. cor.
determined by the old B. T. and data furnished by the
Surveyor General,

Set a basalt stone, 10x10x8 ins., 7 ins. in the ground,
for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which

A fir, 24 ins. diam., bears N.29*E. 30 lks. dist.
marked $\frac{1}{4}$ S B T.

A fir, 6 ins. diam., bears S.73*W. 16 lks. dist.
marked $\frac{1}{4}$ S B T.

Therefore, this line bears N.36*W. and is 36.88 chs. in
length.

From this $\frac{1}{4}$ sec. cor. I run North, on blank line, bet.
secs. 36 and 31.

35.06

Intersect E. and W. line, 575 lks. W. of cor. of secs.
30, 31, 36 and 25, which is a cedar post, 2 ft. above
ground, marked as, but not witnessed as, described by
the Surveyor General.

This cor. not being correct in position, I re-establish
as follows:

Set a cedar post, 4 ft. long, 4 ins. sq., 24 ins. in the
ground for cor. of secs. 25 and 36, marked T 24 S S 36
on SW. and R 2 W S 25 on NW. faces, with 1 notch on S.
and 5 notches on N. edges, from which

A hemlock, 12 ins. diam., bears S.27*W. 15 lks. dist.
marked T 24 S R 2 W S 36 B T.

A hemlock, 12 ins. diam., bears N.16*W. 35 lks. dist.
marked T 24 S R 2 W S 25 B T.

This line, therefore, bears N.9*19'E. and is 35.53 chs.