

County Surveyor's Record, Douglas County, Oregon

74
Retracement of E. Bdy. of T. 24 S., R. 2 W.

CHAINS	<p>in length.</p>
39.60	<p>Thence I run North, on blank line bet. secs. 25 and 30. To a point 61 lks. E. of $\frac{1}{4}$ sec. cor. , which is a basalt stone, marked as described by the Surveyor General. The B. T. in sec. 30 is destroyed. I re-establish cor. to correspond to the following description: Set a basalt rock 18x16x15 ins., 12 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which An oak, 5 ins. diam., bears S.65*W. 20 lks. dist. marked $\frac{1}{4}$ S B T. A madrona, 6 ins. diam., bears N.12*E. 61 lks. dist. marked $\frac{1}{4}$ S B T. Therefore, this line bears N.53*W. and is 39.60 chs. in length. From this $\frac{1}{4}$ sec. cor. I run North on blank line bet. secs. 25 and 30.</p>
38.63	<p>Intersect E. and W. line, 435 lks. W. of cor. of secs. 19, 30, 25 and 24. I find post badly decayed, and accessory trees not agreeing with data furnished by the Surveyor General. This line being incorrect in alinement and position, I re-establish cor. at the same point, as follows: Set a maple post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for cor. of secs. 24 and 25, marked T 24 S S 25 on SW. and R 2 W S 24 on NW. faces, with 2 notches on S. and 4 notches on N. edges, from which A fir, 60 ins. diam., bears S.59*W. 33 lks. dist. marked T 24 S R 2 W S 25 B T. A hemlock, 12 ins. diam., bears N.49*W. 19 lks. dist. marked T 24 S R 2 W S 24 B T. Therefore, this line bears N.6*25'E. and is 38.87 chs. length.</p> <p style="text-align: right;">July 21, 1896.</p>