

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 24 S., R. 4 W.
As surveyed by Harvey Gordon and Charles T. Gordon, Deputy Surveyors,
Under Contract No. 52, Dated Feb. 17, 1855

CHAINS	North, on E. Boundary of Sec. 36	
		Var. 19*21'E.
5.00	Calapooia, course SW.	- 5
28.00	Stream 2 lks. wide, course SE.	+ 15
40.00	Set $\frac{1}{4}$ sec. post from which	+ 50
	A redwood, 40 ins. diam., bears S.80*E. 18 lks. dist.	
	A fir, 15 ins. diam., bears S.76*W. 18 lks. dist.	
78.00	Top of ridge, course SE.	+350
80.00	Set post cor. of secs. 25, 30, 31, 36 from which	- 10
	A fir, 8 ins. diam., bears S.20*W. 55 lks. dist.	
	A fir, 15 ins. diam., bears S.77*E. 15 lks. dist.	
	A fir, 24 ins. diam., bears N.61*E. 10 lks. dist.	
	A fir, 5 ins. diam., bears N. 20*W. 38 lks. dist.	
	Land mountainous	
	Soil 3rd rate	
	Timber, fir & redwood	
	Undergrowth, hazel & laurel	
<p>South Boundary of T. 24 S., R. 3 W. As surveyed by W. H. Byars, Deputy Surveyor, Under Contract No. 152, Dated June 3, 1871</p>		
	Begin at the post, the established cor. to Tps. 24 & 25 S., Rs. 3 & 4 W. Post and witness trees standing. From said cor. I run East on a true line along the S. boundary of Sec. 31.	Var. 19*E.
5.00	Begin ascent	
10.00	Top of spur, course N.	Var. 20*E. +175
12.25	Calapooia Creek 75 lks. wide, course NW.	
20.00	Old blazed line 50 lks. S.	+ 10
21.00	Calapooia Creek 75 lks. wide, Course SW.	
27.25	Begin ascent	+ 10
32.50	Intercept old blazed line	+180
38.95	Old $\frac{1}{4}$ sec. post 12 lks. N. of line	+200
40.00	Set $\frac{1}{4}$ sec. post from which	+200
	A cedar, 28 ins. diam., bears S.50*E. Dist. 22 lks.	
	A fir, 8 ins. diam., bears N.50*W. Dist. 56 lks.	