

County Surveyor's Record, Douglas County, Oregon

West Boundary of T. 24 S., R. 3 W.

CHAINS

chinquapin and salmonberry.

May 19, 1883.

This township is mountainous. It contains a vast amount of valuable timber, consisting chiefly of fir, cedar, hemlock, maple and alder.

There is a thick undergrowth of sallow, vine maple, hazel, manzanita, fir, thimble and salmon berry.

Subdivisions of T. 24 S., R. 3 W.
as surveyed by Laban H. Wheeler, Deputy Surveyor, Under
Contract No. 467, dated Apr. 7, 1883.

Preliminary to commencing this survey, I ran West on a blank line on the South bdy. of sec. 36 and 39.97 chs. found the $\frac{1}{4}$ sec. cor. and at 79.93 chs. found the sec. cor. Thence I run North on a blank line on the East bdy. of sec. 36, and at 40.07 chs. found the $\frac{1}{4}$ sec. cor. and at 80.08 chs. found the sec. cor. My compass will therefore run the same line as the exterior boundaries and the chaining practically agrees.

Survey commenced May 21st, 1883 with a Burts improved solar compass.

I commenced at the cor. to secs. 1, 2, 35 and 36, on the South boundary of the township, which is a hemlock post 4 ins. sq., firmly set in the ground marked T 24 S S 36 on NE., R 3 W S 1 on SE., T 25 S S 2 on SW. and S 35 on NW. faces, with 5 notches on W. and 1 notch on E. edges, from which

A fir, 30 ins. diam., bears N.55*E. 41 lks. dist.
marked T 24 S R 3 W S 36 B T.

A fir, 30 ins. diam., bears S.75*E. 15 lks. dist.
marked T 25 S R 3 W S 1 B T.

A fir, 48 ins. diam., bears S.62*W. 58 lks. dist.
marked T 25 S R 3 W S 2 B T.

A fir, 40 ins. diam., bears N.72*W. 17 lks. dist.
marked T 24 S R 3 W S 35 B T.

Thence I run