

## County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 24 S., R. 4 W.  
 As Surveyed By Harvey Gordon and Charles T. Gardener, Deputy Surveyors  
 Contract No. 52, Dated Feb. 17, 1855

| CHAINS |  |              |
|--------|--|--------------|
|        | <p>This line cannot be extended further East and the East boundary of T. 24 S., R.4 W. cannot be run owing to the high and rugged mountains, therefore run as follows:<br/>           Setting and establishing the proper section and quarter section corner as noted in the field notes of subdivisions<br/>           South bet. secs. 2 &amp; 3 one mile<br/>           East bet. secs. 2 &amp; 11, 60 chains<br/>           (Offset) South 40.00 chains to avoid impassable mountains<br/>           East 20.00 chains to reach the <math>\frac{1}{4}</math> sec. cor. in line bet. secs. 11 &amp; 12<br/>           South 4 miles and 40.00 chains and established the corner of secs. 1, 2, 35 &amp; 36, thence West on Random line on South boundaries of secs. 35, 34, 33, 32 &amp; 31 and 5 miles 0 chains and 20 lks.<br/>           Intersect N. 315 lks. from township corner<br/>           Hence the correction is South 63 lks. per mile and the bearing of the true line N.89*33'E.<br/>           N.89*33'E. on the E boundary of sec. 31</p> |              |
| 0.50   | Top of Ridge course NE   | -50          |
| 40.20  | Set $\frac{1}{4}$ sec. post from which<br>A Black Oak, 12 ins. diam., bears N.11 $\frac{1}{2}$ *W., 351 lks. dist.<br>A Black Oak, 12 ins. diam., bears S.69*W., 532 lks. dist.  | -25          |
| 45.00  | Enter prairie course SW  | -50          |
| 51.50  | Stream, 1 lk. wide, course SE  | -25          |
| 73.50  | Stream, 1 lk. wide, course SW  |              |
| 80.20  | Sec. Post cor. of secs. 5, 6, 31 & 32<br>Drove charred stake raised mound with trench as per instructions<br>Land hilly<br>Soil, 2nd. rate<br>Timber, Oak  |              |
|        | N.89*33'E., on South Boundary of secs. 32  |              |
|        |  | Va. 19*24'E. |