

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 4 W.

CHAINS		
80.00	Set Post cor. of secs. 28, 29, 32 & 33 from which A White Oak, 24 ins. diam., bears N.25*E., 420 lks. dist. Erected Mound drove charred stake Dug Trench with pits as per instructions	
	East on Random line bet. secs. 28 & 33 Va. 18*24'E.	
40.00	Set Temp. $\frac{1}{4}$ sec. Post	
80.00	Intersect Post	
	West on true line bet. secs. 28 & 33	
.50	Leave Prairie course NW	
6.50	Top of Ridge	+50
10.00	Enter Prairie	-50
19.75	Stream 1 lk. wide, course NW	-15
28.50	Road course SW	-5
32.00	Enter Swail course SW	-5
34.00	Leave Swail	
40.00	Set $\frac{1}{4}$ sec. post from which A White Oak, 18 ins. diam., bears S.54*E., 668 lks. dist. Raised Mound drove charred stake Dug Pits with trench as per instructions	
80.00	To sec. cor. Land rolling prairie Soil, 1st. rate	
	North bet. secs. 28 & 29	
14.00	Leave prairie course NW	-10
40.00	Set $\frac{1}{4}$ sec. post from which A White Oak, 10 ins. diam., bears N. 21*E., 46 lks. dist. A Black Oak, 10 ins. diam., bears N.14*W., 44 lks. dist.	+100
47.00	Red Fir 30 ins. diam.	+250