

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 4 W.

See Suppl. Notes

CHAINS	SE; S 14 on SW and S 11 on NW faces with 4 notches on S and 1 notch on E edges and witnessed as described by the surveyor general
	Thence I run East on a Random line bet. secs. 12 & 13
40.00	Set Temp. $\frac{1}{4}$ sec. cor.
79.56	Intersect E bdy. of Tp., 445 lks. N of cor. of secs. 12, 13, 18 and 7 which is a chittem post 2 ft. high, 4 ins. sq. firmly set, marked and witnessed as described by the surveyor general.  At the point of intersection I set a Fir Post 3 ft. long 4 ins. sq. 24 ins. in the ground for closing cor. of secs. 12 & 13 marked C C T 24 S R 4 W on W; S 12 on N and S 13 on S faces with 2 grooves on N and 4 grooves on S faces from which  A Cedar, 12 ins. diam., bears S.73*W., 33 lks. dist. Marked T 24 S R 4 W S 13 B T  A Fir, 8 ins. diam., bears N.5*W., 47 lks. dist., Marked T 24 S R 4 W S 12 B T  Thence I run West on true line bet. secs. 12 & 13 Ascend through heavy Fir Timber
15.50	Top of Spur bears N & S, 175 ft. above sec. cor., a rocky bluff is N  Begin a steep descent
20.40	A rocky canon course S, 100 ft. below top of Spur  Begin ascent
30.00	Top of Spur bears N & S, 225 ft. above bed of canon  Begin descent
39.78'	Set a Cedar Post 3 ft. long 3 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N face from which  A Maple, 10 ins. diam., bears S.58 $\frac{1}{2}$ *W., 31 lks. dist. Marked $\frac{1}{4}$ S B T  A Fir, 20 ins. diam., bears N.78*E., 46 lks. dist. Marked $\frac{1}{4}$ S B T  This cor. is 200 ft. below top of Spur  A Slight ascent along S slope of mountain