

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 4 W.

CHAINS

A Fir, 24 ins. diam., bears S.44*W., 29 lks. dist.,

Marked T 24 S R 4 W S 11 B T

A Fir, 16 ins. diam., bears N.12*W., 93 lks. dist.,

Marked T 24 S R 4 W S 2 B T

Land Mountainous

Soil, rocky, 4th. rate

Timber, Fir, Cedar, Hemlock

Mountainous or heavily timbered land, 20.00 chs.

At the cor. of secs. 1, 2, 11 & 12

Land Mountainous

Soil, rocky, 4th. rate

Timber, Fir, Cedar, Hemlock, Chinquapin, Laurel

Mountainous or heavily timbered land, 40.00 chs.

See Supplementary notes for correction

Weather does not permit taking of latitude

East on a Random line bet. secs. 1 & 12

40.00 Set Temp. $\frac{1}{2}$ sec. cor.

80.25 Intersect E bdy. of Tp. 624 lks. N of cor. of secs. 1, 12

6 & 7 which is a Yew Post 2 ft. high, 4 ins. sq. firmly set, marked and witnessed as described by the surveyor general

At the point of intersection I set a Cedar Post 3 ft.

long, 4 ins. sq. 24 ins. in the ground for closing cor.

of secs. 12 and 1, marked CC T 24 S R 4 W on W; S 1 on

N and S 12 on S faces with one groove on N and 5 grooves

on S faces from which

A Fir, 36 ins. diam., bears N.8 $\frac{1}{2}$ *W., 55 lks. dist.

Marked T 24 S R 4 W S 1 B T

No other tree within limits; dug a pit 24x18x12 ins. S

3 ft. and W of post 7 ft. dist., and raised mound of

earth 4 ft. base, 2 ft. high W of cor.

September 19, 1896

Thence I run

West on true line bet. secs. 1 & 12

Descend slightly mountain slope covered mostly by burnt