

Subdivisions of T. 24 S., R. 4 W.

CHAINS	<p>Descend West slope of mountain covered heavily by Fir Timber</p> <p>20.85 A Creek, 25 lks. wide, course S, 300 ft. below sec. cor. Begin steep ascent</p> <p>31.50 More gradual ascent of E slope</p> <p>40.24 Set a sandstone 15x8x6 ins., 10 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on N face from which</p> <p style="padding-left: 40px;">A Cedar, 18 ins. diam., bears S.9*W., 57 lks. dist., Marked $\frac{1}{4}$ S B T</p> <p style="padding-left: 40px;">A Cedar, 20 ins. diam., bears N.30*E., 38 lks. dist., Marked $\frac{1}{4}$ S B T</p> <p>This cor. is 275 ft. above creek, keep on ascending</p> <p>42.00 Top of Spur, bears N & S, 60 ft. above $\frac{1}{4}$ sec. cor; begin descent</p> <p>49.80 A Branch 2 lks. wide, course SE, 75 ft. below top of spur Begin ascent</p> <p>59.00 Top of ridge, bears N & S, 150 ft. above branch Begin descent of W slope</p> <p>73.70 A Branch 3 lks. wide, course SW, 300 ft. below top of ridge Slight ascent of W slope</p> <p>80.48 The cor. of secs. 10, 11, 14 & 15</p> <p>Land Mountainous</p> <p>Soil, gravelly, 3rd. rate</p> <p>Timber, Fir, Cedar, Hemlock</p> <p>Mountainous or heavily timbered land, 80.48 chs.</p> <p>The weather prevents taking lat.</p> <hr/> <p>N.89*30'W., on Random bet. secs. 10 & 15</p> <p>40.00 Set Temp. $\frac{1}{4}$ sec. cor.</p> <p>79.80 Intersect N & S line, 47 lks. N of cor. of secs. 9, 10, 15 & 16 which I reestablish by setting a Fir Post, 3 ft. long, 4 ins. sq., 24 ins. in the ground marked T 24 S S10 on NE R 4 W S 15 on SE; S 16 on SW and S 9 on NW faces with 4 notches on S and 3 notches on E edges and witness- ed as described by the surveyor general</p>
--------	---

September 21, 1896

See Suppl. Notes.