

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 4 W.

CHAINS

At the cor. of secs. 9, 10, 15 & 16
 Thence I run
 S.89*50'E., on a true line bet. secs. 10 & 15
 Ascend slope of mountain, covered heavily by Fir Timber
 3.30 Top of ascent of ridge, bears SE & NW, 20 ft. above sec.
 cor.
 Begin very steep descent of NE slope.
 7.30 Descent becomes more gradual.
 26.30 Top of Spur, bears N & S, 300 ft. below top of ridge
 39.90 Set A Fir Post 3 ft. long, 3 ins. sq., 24 ins. in the
 ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on N face from which
 A Fir, 24 ins. diam., bears N.63 $\frac{1}{2}$ *E., 13 lks. dist.,
 Marked $\frac{1}{4}$ S B T
 A Fir, 20 ins. diam., bears S.61*E., 23 lks. dist.,
 Marked $\frac{1}{4}$ S B T
 This cor. stands 75 ft. below top of spur
 44.40 A Canon, course N, 120 ft. below $\frac{1}{4}$ sec. cor., begin steep
 ascent of W slope
 47.30 Top of Spur, bears N & S, 75 ft. above canon
 Begin gradual descent along N slope
 59.80 Descent changes to NE slope
 78.30 A Stream 8 lks. wide, course SE 300 ft. below Spur
 79.80 The cor. of secs. 10, 11, 14 & 15
 Land Mountainous
 Soil, gravelly, Clay, 2nd. rate
 Timber, Fir, Cedar, Hemlock
 Mountainous or heavily timbered Land, 79.80 chs.

AT the cor. of secs. 10, 11, 14 & 15
 Thence I run
 N.0*1'W., on a random line bet. secs. 10 & 11
 40.00 Set Temp $\frac{1}{4}$ sec. cor.
 80.23 Intersect E & W line, 19 lks. W of cor. of secs. 2, 3, 10
 & 11, which I reestablish by setting a Cedar Post 3 ft.
 long, 4 ins. sq., 24 ins. in the ground marked T 24 S S
 2 on NE, R 4 W S 11 on SE, S 10 on SW and S 3 on NW

See Suppl. Notes.