

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 4 W.

CHAINS	<p>Land Mountainous</p> <p>Soil, gravelly, 3rd. rate</p> <p>Timber, Fir, Hemlock, Cedar</p> <p>Mountainous or heavily timbered land, 80.18 chs.</p>
	<p>S.89*30'W., on Random line bet. secs. 4 & 9</p>
40.00	<p>Set Temp. $\frac{1}{2}$ sec. cor.</p>
80.36	<p>Intersect N & S line, 48 lks. S of cor. to secs. 4, 5, 8 & 9 being a Fir Post, 4 ins. sq. set by the Co. in 1884 surveyor marked and witnessed as described by the surveyor general</p>
	<p style="text-align: right;">September 24, 1896</p>
	<p>At the cor. of secs. 4, 5, 8 & 9</p>
	<p>Thence I run</p>
	<p>N.89*51'E., on true line bet. secs. 4 & 9</p>
	<p>Ascend a very steep bluff</p>
2.00	<p>Top of mountain ridge, bears N & S, 125 ft. above sec. cor; a fence in prairie bears due W, about 2 miles distant; the schoolhouse in the town of Oakland bears S.44*W.</p>
	<p>Begin to descend the E slope of mountain, covered heavily with Fir Timber, bears N & S</p>
40.18	<p>A Point 400 ft. below top of mountain, I set a Fir Post 3 ft. long 3 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on the N face from which</p> <p style="padding-left: 40px;">A Fir, 10 ins. diam., bears N.6*W., 5 lks. dist., Marked $\frac{1}{4}$ S B T</p> <p style="padding-left: 40px;">A Fir, 24 ins. diam., bears S.25*E., 39 lks. dist., Marked $\frac{1}{4}$ S BT</p>
	<p>Keep on descending</p>
59.30	<p>A Branch 3 lks. wide, course N, 500 ft. below $\frac{1}{4}$ sec. cor. Begin to ascend a steep NW slope</p>
71.60	<p>Top of Spur, course NE & SW, 100 ft. above branch, begin to descend E slope</p>
80.36	<p>The cor. of secs. 3, 4, 9 & 10, 200 ft. below top of spur</p> <p>Land Mountainous</p>