

-H-

 County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 24 S., R. 6 W.

CHAINS	South on West Boundary of Sec. 31 Va. 18*45'E.	
18.80	A stream 5 lks. wide, course East	-600
37.00	Top of spur slopes NE	+800
40.00	Set $\frac{1}{2}$ sec. post, from which	-30
	A fir, 12 ins. diam., bears S.87*E., 44 lks. dist.	
	A fir, 8 ins. diam., bears S.3*W., 59 lks. dist.	
53.00	Top of ridge, course NW & SE. Begin to descend SW slope	+200
80.00	Set post cor. to Tps. 24 & 25 South & bet. Rgs. 6 & 7, from which	
	A fir, 36 ins. diam., bears S.80 $\frac{1}{2}$ *W., 89 lks. dist.	
	A fir, 30 ins. diam., bears N.7 $\frac{1}{2}$ *W., 122 lks. dist.	
	A fir, 28 ins. diam., bears N.56 $\frac{1}{2}$ *E., 97 lks. dist.	
	A fir, 44 ins. diam., bears S.18*E., 70 lks. dist.	
	Land, all Rocky Mountains. Soil, 3rd rate Timber, fir, cedar, yew, laurel, etc. Undergrowth, hazel, fir, fern, briars, etc. The rock on this line is a compact sand stone	
	May 17, 1853	
South Bdy. of T. 24 S., R. 6 W., Same Deputies & Contract		
Random on South Boundary		
East on random on the South boundaries of Secs. 31, 32, 33, 34, 35 & 36		
Set temporary sec. and $\frac{1}{4}$ sec. posts & at 6 miles 1 ch. and 75 lks. intersect East boundary 80 lks. South of Tp. cor. Therefore the correction will be 175 lks. East and 13 $\frac{1}{2}$ lks. North per mile and the course S.89*54*W.		
True South Boundary		
S.89*54*W. on South Boundary of Sec. 36		
Va. 18*30'E.		
18.00	Top of hill N & S begin to descend	+150
40.00	Set $\frac{1}{4}$ sec. post, from which	-400
	A B oak, 12 ins. diam., bears S.12*W., 68 lks. dist.	
	A W oak, 20 ins. diam., bears N.19*W., 102 lks. dist.	
58.75	A road at Base of hill, course N & S	-250
62.50	A stream 15 lks. wide, course South	-25
65.50	A road, course NW & SE. Begin to ascend hill	