

32  
County Surveyor's Record, Douglas County, Oregon

3159

Subdivisions of T. 24 S., R. 6 W.  
As surveyed by William R. Whipple, Deputy Surveyor  
Under Contract No. 577, Dated July 18, 1891

CHAINS	<p>Survey commenced August 14, 1891</p> <p>From the established corner to Secs. 29, 30, 31 &amp; 32 T. 24 S., R. 6 W.</p> <p>Post gone, I reestablish same by setting fir post 4 ft. long 4 ins. sq. 24 ins. in ground marked T 24 S S 29 on NE., R 6 W S 32 on SE., S 31 on SW., S 30 on NW faces with 1 notch on the South and 5 notches on the E edges, from which</p> <p style="padding-left: 40px;">A white oak, 20 ins. diam., bears N.69<math>\frac{1}{2}</math>*E., 454 lks. dist. Marked T 24 S R 6 W S 29 B T</p> <p style="padding-left: 40px;">A W oak, 11 ins. diam., bears S.46<math>\frac{3}{4}</math>*E., 362 lks. dist. Marked T 24 S R 6 W S 32 B T</p> <p style="padding-left: 40px;">A W oak, 13 ins. diam., bears S.66<math>\frac{3}{4}</math>*W., 50 lks. dist. Marked T 24 S R 6 W S 31 B T</p> <p style="padding-left: 40px;">A W oak, 13 ins. diam., bears N.89*W., 68 lks. dist. Marked T 24 S R 6 W S 30 B T</p> <hr/> <p>Took latitude at noon and found it to be 43*26' North</p> <p>Instrument used</p> <p>An engineers transit made by Edmond Draper of Philadelphia Pa. and having a solar attachment made and put on by W &amp; D E Gurley of Troy, N. Y.</p> <p>Thence I run</p> <p>S.89*54'W on random line bet. secs. 30 &amp; 31</p> <p style="padding-left: 100px;">Va. 20*39'E</p> <p>40.00 Set temporary <math>\frac{1}{2}</math> sec. corner</p> <p style="padding-left: 100px;">Va. 20*30'E</p> <p>81.57 Intersect West boundary of Township 15 lks. north of cor. to secs. 25, 30, 31 &amp; 36. Post gone, reestablish same by setting a fir post, 4 ft. long, 4 ins. sq. 24 ins. in the ground, marked T 24 S S 30 on NE, R 6 W S 31 on SE, R 7 W S 36 on SW, S 25 on NW faces, with 1 notch on S and 6 notches on E edges, from which</p>
--------	--