

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 6 W.

CHAINS		
29.75	A spring bears West 30 lks. dist., runs NW	452
40.00	Set a yew post, 4 ft. long, 4 ins. sq. 24 ins. in the ground marked $\frac{1}{4}$ S on W face, from which	
	A hemlock, 12 ins. diam., bears N.42*15'W., 19 lks. dist. Marked $\frac{1}{4}$ S B T	
	A fir, 56 ins. diam., bears N.65*15'E., 47 lks. dist. Marked $\frac{1}{4}$ S B T	
40.25	Enter stream 4 lks. wide	
41.30	Leave same. Runs from here N.20*W.	13
55.00	Top of ascent & descend	43
59.70	Enter stream 4 lks. wide	
61.00	Leave same, runs N.20*W.	182
65.00	Ascend	75
	Descend	
69.15	Stream 2 lks. wide, course NW	17
73.00	Ascend	14
	Descend	
79.64	Stream 1 lk. wide, course N.30*W., from spring 70 lks. SE	40
80.00	Set a cedar post, 4 ft. long 4 ins. sq. 24 ins. in the ground, for cor. to secs. 4, 5, 8 & 9, marked T 24 S S 4 on NE, R 6 W S 9 on SE, S 8 on SW, and S 5 on NW faces with 5 notches on the S and 4 notches on the E edges, from which	
	A fir, 36 ins. diam., bears N.44*E., 35 lks. dist.	
	Marked T 24 S R 6 W S 4 B T	
	A maple, 18 ins. diam., bears S.29*50'E., 32 lks.	
	dist. Marked T 24 S R 6 W S 9 B T	
	A fir, 20 ins. diam., bears S.18*W., 56 lks. dist.	
	Marked T 24 S R 6 W S 8 B T	
	A cedar, 4 ins. diam., bears N.26*10'W., 15 lks.	
	dist. Marked T 24 S R 6 W S 5 B T	
	Heavily timbered with fir and cedar, 80.00 chs.	