

County Surveyor's Record, <sup>64-</sup>Douglas County, Oregon

Subdivisions of T. 24 S., R. 6 W.

CHAINS		
35.25	Stream 8 lks. wide, course South	-560
41.74	A dogwood, 6 ins. diam. which I marked $\frac{1}{4}$ S on the North side for $\frac{1}{4}$ sec. cor., from which A cedar, 15 ins. diam., bears N.77*W., 7 lks. dist. Marked $\frac{1}{4}$ S B T A fir, 14 ins. diam., bears S.22*40'E., 49 lks. dist. Marked $\frac{1}{4}$ S B T	
70.00	Top of ascent Descend	+404
77.00	Foot of descent	-293
81.74	The corner to secs. 5, 6, 7 & 8 Heavily timbered with fir, cedar & laurel Dense undergrowth of fir, hazel, vine-maple, arrowwood, laurel, manzinita, & salal, 81.74 chs. Land, mountainous Soil, 2nd and 3rd, and 4th rates	+57
	Sept. 11, 1891	

	N.0*4 $\frac{1}{2}$ 'W on random line bet. secs. 5 & 6 Va. 20*42'E.	
40.00	Set temporary $\frac{1}{4}$ sec. cor.	
79.27	Intersect N. boundary of township 145 lks. E of cor. to secs. 5, 6, 31 & 32 which is cedar post, 4 ft. long, 4 ins. sq. 24 ins. in the ground for cor. to secs. 5, 6, 31 & 32 marked T 23 S S 32 on NE, T 24 S S 5 on SE, R 6 W S 6 on SW and S 31 on NW faces with 6 notches on the S and 5 notches on the E edges, from which, the original bearing trees are as follows: A fir, 15 ins. diam., bears N.22*E., 53 lks. dist. Marked T 23 S R 6 W S 32 B T A fir, 10 ins. diam., bears S.47*E., 10 lks. dist. Marked T 24 S R 6 W S 5 B T	