

Exterior lines of T 24 S., R 8 W., W.M.

CHAINS	
	The above cedar, bears S.70*E., 25 lks. dist., marked T.24 S R 8 W S 30 B T.
	and mark new trees as follows.
	A Maple, 10 ins. diam., bears N.17*E., 75 lks. dist. marked T 24 S R 7 W S 19 B T.
	A Maple, 8 ins. diam., bears S.88*W., 57 lks. dist. marked T 24 S R 8 W S 25 B T.
	A Fir, 60 ins. diam., bears N.51*W., 79 lks. dist., marked T 24 S R 8 W S 24 B T.
	Thence I run
	North on range line bet. secs. 19 and 24.
	Va. 20*E.
	Ascend through heavy timber and dense undergrowth about 75 ft. to
9.50	Top of ridge, course W.
	Descend about 100 ft. to
27.00	Foot of hill, course E and W., thence over bench.
37.50	Leave bench and descend, course E and W.
40.00	Set a post, 3½ ft. long, 3 ins. sq., 24 ins. in the ground for ¼ sec. cor., marked ¼ S on W face, from which
	A Fir, 36 ins. diam., bears S.78*E., 141 lks. dist. marked ¼ S B T.
	A Fir, 18 ins. diam., bears S.75*W., 92 lks. dist., marked ¼ S B T.
42.00	A brook, 1 lk. wide, flows NE.
56.80	A creek, 5 lks. wide, flows NW about 200 ft. below bench, ascend about 150 ft. to
77.50	Top of ridge, course NW., descend.
80.00	Set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for cor. to secs. 18, 19, 13 and 24., marked
	T 24 S S 18 on NE.
	R 7 W S 19 on SE.
	R 8 W S 24 on SW and
	S 13 on NW faces with 3 notches on S and N edges, from which
	A Fir, 30 ins. diam., bears N.21*E., 213 lks.