

Exterior lines of T 24 S., R 8 W., W.M.

CHAINS

dist., marked T 24 S R 7 W S 18 B T.

A Fir, 24 ins. diam., bears S.80°E., 180 lks. dist.,
marked T 24 S R 7 W S 19 B T.

A Fir, 14 ins. diam., bears S.76°W., 65 lks. dist.,
marked T 24 S R 8 W S 24 B T.

A Fir, 14 ins. diam., bears N.58°W., 136 lks. dist.,
marked T 24 S R 8 W S 13 B T.

Land rolling bench, 10.50 chs.

Land mountainous, 69.50 chs.

Heavily timbered with fir and hemlock, 80.00 chs.

Dense undergrowth of vinemaple, hazel and sallow, 80.00
chs.

Soil sandy and rocky, 3rd and 4th rate.

North on E boundary of sec. 13.

Va. 20°E.

Descend through heavy timber and dense undergrowth about
200 ft. to

9.25 A creek, 8 lks. wide, flows SW., ascend about 300 ft. to

38.50 Top of ridge, course SW., descend.

40.00 Set a post, 3½ ft. long, 3 ins. sq., 24 ins. in the
ground for ¼ sec. cor., marked ¼ S on W face, from
which

A Fir, 18 ins. diam., bears N.81°E., 21 lks. dist.,
marked ¼ S B T.

A Fir, 16 ins. diam., bears N.55°W., 56 lks. dist.,
marked ¼ S B T.

48.80 A spring branch, 2 lks. wide, flows NW.

61.50 A spring branch, 2 lks. wide flows SW about 150 ft. below
top of ridge, ascend about 200 ft. to

71.45 Top of ridge, course NW., descend.

79.10 Rocky bluff about 40 ft. high, course E and W.

79.45 Foot of hill, course E and W., about 200 ft. below top
of ridge, thence over bench.