Subdivisions of T 24 S., R 7 W., W.M.

CHAINS		
	N and 1 notch on S edges, from which	
	A Fir, 20 ins. diam., bears N.23*E., 37 lks. dist., marked T 24 S R 6 W S 30 B T.	See-corrected field notes
	A Fir, 18 ins. diam., bears S.3*E., 36 lks. dist., marked T 24 S R 6 W S 31 B T.	
	A Fir, 10 ins. diam., bears S.52½*W., 45 lks. dist., marked T 24 S R 7 W S 36 B T.	
	A Fir, 20 ins. diam., bears N.50*W., 34 lks. dist., marked T 24 S R 7 W S 25 B T.	
	At this point of intersection, I set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for closing cor. to secs. 25 and 36 marked C C T 24 S R 7 W on W., S 25 on N and S 36 on S with 5 notches on N and 1 notch on S faces from which	
	A Cedar, 10 ins. diam., bears N.68½*W., 39 lks. dist., marked T 24 S R 7 W S 25 B T.	
	A Fir, 36 ins. diam., bears S.28*W., 19 lks. dist., marked T 24 S R 7 W S 36 B T.	
	A Fir, 36 ins. diam., bears S.40*E., 35 lks. dist., marked T 24 S R 7 W C C S 25 and 36 B T.	
	Thence I run	
	West on a true line bet. secs. 25 and 36.	
	Va. 20*34'E.	
	Ascend through timber.	
8.00	Top of Tyee Mountain, and descend.	+200
11.49	A Fir, 40 ins. diam., marked with 2 notches on E and W sides.	
40.14	Set a post, 3 ft. long, 3 ins. sq., 24 ins. in the ground for ¼ sec. cor., marked ¼ S on N face, from which	
	A Cedar, 24 ins. diam., bears N.25*E., 22 lks. dist. marked ¼ S B T.	
	A Cedar, 24 ins. diam., bears S.70½*E., 78 lks. dist. marked ¼ S B T.	