

Subdivisions of T 24 S., R 7 W., W.M.

CHAINS
81.05

The cor. to secs. 4, 5, 8 and 9, which is a fir, 24 ins. diam., marked T 24 S S 4 on NE., R 7 W S 9 on SE., S 8 on SW., and S 5 on NW., sides, with 5 notches on S. and 4 notches on E sides, from which

A Fir, 15 ins. diam., bears N.1°E., 34 lks. dist., marked T 24 S R 7 W S 4 B T.

A Fir, 24 ins. diam., bears S.45°E., 2 lks. dist.; marked T 24 S R 7 W S 9 E T.

A Fir, 20 ins. diam., bears S.45°W., 3 lks. dist., marked T 24 S R 7 W S 8 E T.

A Fir, 24 ins. diam., bears N.5°W., 6 lks. dist., marked T 24 S R 7 W S 5 B T.

Dec. 11, 1893

Beginning at the cor. to secs. 15, 16, 21 and 22, which is a post, 4 ins. sq., marked T 24 S S 15 on NE., R 7 W S 22 on SE., S 21 on SW., and S 16 on NW., faces, with 3 notches on S. and E. edges, from which

An Oak, 18 ins. diam., bears N.50°E., 186 lks. dist. marked T 24 S R 7 W S 15 B T.

An Oak, 18 ins. diam., bears S.60°E., 170 lks. dist. marked T 24 S R 7 W S 22 E T.

An Oak, 30 ins. diam., bears S.5°W., 511 lks. dist. marked T 24 S R 7 W S 21 B T.

An Oak, 18 ins. diam., bears N.1°W., 645 lks. dist. marked T 24 S R 7 W S 16 B T.

I run

East bet. secs. 15 and 22.

Va. 20°35'E.

.50 Enter fir thicket and descend.

20.00 Enter river bottom.

25.46 Intersect the left bank of the Umpqua River.

The meander cor. being gone, I set a post, 4 ft. long, 4 ins. sq., 24 ins. in the ground for meander cor. to