

Subdivisions of T 24 S. R 7 W. W.M.

CHAINS
81.00

The cor. to secs. 19, 20, 29 and 30, which is a post, 4 ins. sq., marked T 24 S S 20 on NE., R 7 W S 29 on SE., S 30 on SW., and S 19 on NW., sides, with 2 notches on S and 5 notches on E. edges, from which

An Oak, 20 ins. diam., bears N.89°E., 665 lks. dist. marked T 24 S R 7 W S 20 P T.

An Oak, 18 ins. diam., bears S.89°E., 670 lks. dist. marked T 24 S R 7 W S 29 B T.

An Oak, 18 ins. diam., bears N.3°W., 437 lks. dist. marked T 24 S R 7 W S 19 L T.

No tree SW., of cor.

The reference notes represent this line as being 79.98 chs. instead of 81 chs. in length.

North bet. secs. 19 and 20.

Va. 20°30'E.

40.48 The $\frac{1}{2}$ sec. cor., which is a post, 3 ins. sq., marked $\frac{1}{2}$ S on W. side, from which

A Fir, 50 ins. diam., bears N.88°E., 50 lks. dist., marked $\frac{1}{2}$ S E T.

A Myrtle, 14 ins. diam., bears S.50°W., 17 lks. dist. marked $\frac{1}{2}$ S B T.

80.90 The cor. to secs. 17, 18, 19 and 20, instead of 80 chs., as per reference notes.

May 28, 1894.

21 miles, 40 chs. and 2 lks. of the subdivisional lines, 18 chs. and 98 lks. of the connecting lines, 4 chs. and 75 lks. of the meander lines, and 4 miles, 78 chs. and 92 lks. of the resurveyed lines, run over mountainous lands or through timber, or dense underbrush.

GENERAL DESCRIPTION:

The portion of the township embraced in this survey is