

88  
County Surveyor's Record, Douglas County, Oregon

Correction and Explanation of the Survey of T. 24 S., R. 7 W.

CHAINS

A fir, 14 ins. diam., bears N.62\*E., 23 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

A cedar, 30 ins. diam., bears South, 48 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

I destroy original  $\frac{1}{4}$  cor. and continue E.

41.65 A stream, 3 lks. wide, course N.80\*W.

62.00 A ridge, course N.10\*W and S.10\*E., 250 ft. above  $\frac{1}{4}$  cor.

65.00 Gulch, course NE.

76.00 Spur, slopes N.

80.26 Intersect at closing cor. to secs. 3 and 10.

I therefore make the same cor. to secs. 3, 4, 9 and 10,  
by removing C C from cor. stone and bearing trees, S 3  
and 10 from the SW B T., and marking S 9 on same.

A fir, 40 ins. diam., bears N.34\*W., 52 lks. dist.,  
which I mark T 24 S R 7 W S 4 B T.

Land, mountainous.

Soil, 3rd rate.

Timber, fir, cedar, hemlock, laurel, with a dense under-  
growth of hazel, vine maple, arrowwood, sallal, fern,  
briars.

June 14, 1896.

Retracement of the North Boundary of T. 25 S., R. 7 W., W.M.  
As surveyed by William P. Heydon, U.S. Deputy Surveyor,  
Under contract No. 656, dated May 21, 1896.

To the established cor. of secs. 4 and 5 on N bdy. of  
T. 25 S., R. 7 W., which is a post marked and witnessed  
as described by the Surveyor General.

From the meridian thus determined, I turn 90\*E., and run  
E to retrace line run by Wm. R. Whipple, bet. Tps. 24  
and 25 S., R. 7 W., North bdy. of sec. 4.

Va.20\*E.

Descend.

.79 Closing cor. to secs. 32 and 33, which is a post, marked  
and witnessed as described by the Surveyor General.

12.00 Porter Creek, 5 lks. wide, course N.15\*W., 200 ft. below  
cor.

-50

+100