

## County Surveyor's Record, Douglas County, Oregon

## Resurvey of South Boundary T. 24 S., R. 8 W.

CHAINS

A Hemlock, 6 ins. diam., bears S.40\*W., 14 lks.  
dist. marked  $\frac{1}{2}$  S B T.

A Hemlock, 24 ins. diam., bears N.40\*W., 31 lks.  
dist. marked  $\frac{1}{2}$  S B T.

48.00 Foot of rocky hill, course SW and NE. Ascend about  
300 ft. to

65.00 Top of ridge, course N. Descend.

72.25 The old established cor. to Secs. 4, 5, 32 and 33, which  
is a post 4 ins. sq., 2 ft. above ground, marked  
T 24 S S 33 on NE., T 25 S S 4 on SE., R 8 W S 5 on SW  
and S32 on NW faces, with 4 notches on East and 2  
notches on West edges, from which,

A Fir, 24 ins. diam., bears N.60\*E., 28 lks.  
dist., marked T 24 S R 8 W S 33 - B T.

A Fir, 48 ins. diam., bears S.5\*E., 39 lks.  
dist., marked T 25 S R 8 W S 4 - B T.

A Fir, 30 ins. diam., bears S.88\*W., 90 lks.  
dist., marked T 25 S R 8 W S 5 - B T.

A Fir, 30 ins. diam., bears N.89\*W., 105 lks.  
dist., marked T 24 S R 8 W S 32 - B T.

I destroy marks on both post and trees referring to  
Secs. 32 and 33.

80.00 Set a sandstone 22 x 8 x 6 ins., 16 ins. in the ground  
for cor. to secs. 32 and 33, marked with 4 notches  
on East and 2 notches on West edges, from which

A Fir, 6 ins. diam., bears N.73\*E., 49 lks.  
dist., marked T 24 S R 8 W S 33 - B T.

A Fir, 48 ins. diam., bears N.42\*W., 91 lks.  
dist., marked T 24 S R 8 W S 32 - B T.

A Fir, 60 ins. diam., bears S.60\*E., 31 lks.  
dist., marked T 24 S R 8 W S 32 and 33 - B T.

Land, broken.

Soil, 2nd and 4th rate.

Heavily timbered with Fir, Hemlock and Cedar. 80.00 chs.  
dense undergrowth of sallal, vinemaple and hazel.

80.00 chs.

May 17th, 1894.