

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 8 W.

CHAINS

80.48

Intersect East and West line, 49 lks. East of cor. to Secs. 25, 26, 35 and 36, which is a post 4 ins. sq. firmly set in the ground, marked T 24 S S 25 on NE., R 8 W S 36 on SE., S 35 on SW and S 26 on NW faces, with 1 notch on South and East edges, from which

A Fir, 18 ins. diam., bears S.80°E., 42 lks. dist., marked T 24 S R 8 W S 36 - B T.

A Fir, 18 ins. diam., bears N.85°E., 52 lks. dist., marked T 24 S R 8 W S 25 - B T.

A Fir, 60 ins. diam., bears N.73°W., 35 lks. dist., marked T 24 S R 8 W S 26 - B T.

A Chinquapin, 6 ins. diam., bears S.25°W., 28 lks. dist., marked T 24 S R 8 W S 35 - B T.

Thence I run

S.0°22'E. on a true line bet. Secs. 35 and 36.

Va. 19°E.

Descend through heavy timber and dense undergrowth about 100 ft. to

18.00 Foot of hill and enter bottom, course NW. and SE.

27.00 A Creek, 50 lks. wide, flows SE.

27.50 Foot of hill, course NW and SE.

Leave bottom and ascend.

36.20 A Spring branch, 1 lk. wide, flows SE.

40.00 Top of ridge, course East about 250 ft. above foot of hill.

At this point I again made careful search but could find no trace of the old $\frac{1}{4}$ sec. cor.

Set a basalt stone 24 x 12 x 4 ins., 18 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on West face, from which

A Laurel, 16 ins. diam., bears N.21°E., 100 lks. dist., marked $\frac{1}{4}$ S B T.

A Fir, 20 ins. diam., bears N.7 $\frac{1}{2}$ °W., 60 lks. dist., marked $\frac{1}{4}$ S B T.