

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 8 W.

CHAINS

From the cor. to Secs. 2, 3, 34 and 35 on the South Bdy. of the Tp. which is a Fir tree, 36 ins. diam., marked T 24 S S 35 on NE., R 8 W S 2 on SE., T 25 S S 3 on SW., and S 34 on NW. sides, with 2 notches on East and 4 notches on West sides, from which

A Fir, 60 ins. diam., bears N.64*E., 52 lks. dist., marked T 24 S R 8 W S 35 - B T.

A Fir, 60 ins. diam., bears S.30*E., 38 lks. dist., marked T 25 S R 8 W S 2 - B T.

A Fir, 12 ins. diam., bears S.15*W., 29 lks. dist., marked T 25 S R 8 W S 3 - B T.

A Fir, 8 ins. diam., bears N.8*W., 22 lks. dist., marked T 24 S R 8 W S 34 - B T.

I run

N.0*2'W. bet. Secs. 34 and 35.

Va. 20*E.

Ascend through heavy timber and dense undergrowth about 75 ft. to

8.00 Top of ridge, course NE.
Descend about 400 ft. to

24.00 A Spring branch, 1 lk. wide, flows NE.
Ascend about 200 ft. to

31.50 Top of ridge, course NE.
Descend about 100 ft. to

36.00 Bottom of ravine, course NE.
Ascend about 20 ft. to

37.00 Top of hill, course
Thence along bench to

39.50 Begin to descend.

40.00 Set a post $3\frac{1}{2}$ ft. long, 3 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S on W face, from which

A Cedar, 10 ins. diam., bears S.21 $\frac{1}{2}$ *E., 14 lks. dist., marked $\frac{1}{4}$ S B T.