

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 24 S., R. 8 W.

CHAINS

N.0*3'W., bet. Secs. 32 and 33.

Va. 20*E.

Descend through heavy timber and dense undergrowth
about 10 ft. to

0.50 A Creek, 10 lks. wide, flows NW.

Ascend about 300 ft. to

40.00 Top of ridge, course NE.

Set a sandstone 24 x 12 x 5 ins., 18 ins. in the
ground for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face, from
which

A Fir, 36 ins. diam., bears N.46 $\frac{1}{2}$ *W., 100 lks.
dist., marked $\frac{1}{4}$ S B T.

A Laurel, 16 ins. diam., bears S.46 $\frac{1}{2}$ *E., 22 lks.
dist., marked $\frac{1}{4}$ S B T.

Descend about 300 ft. to

70.00 Spring branch, 1 lk. wide, flows NW.

Ascend about 150 ft. to

80.00 Top of ridge, course NE.

Set a post 4 ft. long, 4 ins. sq., 24 ins. in the
ground for cor. to Secs. 28, 29, 32 and 33, marked
T 24 S S 28 on NE., R 8 W S 33 on SE., S 32 on SW.,
and S 29 on NW faces, with 1 notch on South and
4 notches on East edges, from which

A Fir, 18 ins. diam., bears N.75*E., 28 lks.
dist., marked T 24 S R 8 W S 28 - B T.

A Fir, 18 ins. diam., bears S.12*E., 110 lks.
dist., marked T 24 S R 8 W S 33 - B T.

A Fir, 40 ins. diam., bears S.57*W., 26 lks.
dist., marked T 24 S R 8 W S 32 - B T.

A Yew, 20 ins. diam., bears N.50*W., 60 lks.
dist., marked T 24 S R 8 W S 29 - B T.

Land, mountainous. 80.00 chs.

Soil, sandy and rocky, 3rd and 4th rate.

Heavily timbered with Fir and Hemlock. 80.00 chs.

Dense undergrowth of vinemaple, salal, and hazel.

80.00 chs.