

Subdivisions of T. 24 S., R. 8 W.

CHAINS

54 Miles, 70 chs. and 90 lks. of the subdivisional lines in this Township run over mountainous lands or through heavy timber or dense undergrowth.

- - - GENERAL DESCRIPTION - - -

The land in this Township is rough and broken and is heavily timbered with Fir of good quality. The soil is mostly 3rd and 4th rate. The entire Township is well watered by numerous small streams.

Retracement of South Boundary of T. 24 S., R. 8 W.  
Surveyed by Morris Wygant, Compassman for  
Zachariah M. Derrick, U. S. Deputy Surveyor,  
under Contract No. 779, dated Feb. 7, 1908.

At the cor. Secs. 2, 3, 34 and 35, on the S. bdy. of T. 24 S., R. 8 W. The tree cor. is burnt down, a burnt snag, marked T 24 S R 8 W S 34 B T, bears NW., a burnt snag, marked S 35 T 24 S R 8 W B T, bears NE., a burnt snag, marked T 25 S R 8 W S 2 B T, bears SE., a burnt snag, marked T 25 S R 8 W S 3 B T, bears SW. I destroy all traces of the old cor. and cut off all marks on the burnt snags, and at the exact point of old cor. I set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of Secs. 2 and 3, 34 and 35, marked T 24 S S 25 on NE., R 8 W S 2 on SE., T 25 S S 3 on SW. and R 8 W S 34 on NW. face, with 2 grooves on E. and 4 grooves on W. edges, from which

A Fir, 60 ins. diam., bears N.60°E., 39 lks.  
dist., marked T 24 S R 8 W S 35 B T.

A Fir, 18 ins. diam., bears S.5°E., 50 lks.  
dist., marked T 25 S R 8 W S 2 B T.

A Cedar, 30 ins. diam., bears S.29°W., 25 lks.  
dist., marked T 25 S R 8 W S 3 B T.