

County Surveyor's Record, Douglas County, Oregon

Retracements of South Boundary T. 24 S., R. 8 W.

CHAINS

A Fir, 14 ins. diam., bears N.15*W., 27 lks.
dist., marked T 24 S R 8 W S 34 B T.

Thence I run

West, retracing S. bdy. of Sec. 34

40.00 find no trace of old $\frac{1}{2}$ sec. cor., after most diligent
search.

77.35 Intersect the old cor. of Secs. 3, 4, 33 and 34,
which is a post, firmly set, marked and witnessed
as described by the Surveyor General, and which
I afterward change to refer to Secs. 33 and 34,
T 24 S., R. 8 W. only.

June 17th, 1911.

2

At the cor. of Secs. 3, 4, 33 and 34, on the S. bdy.
of T. 24 S., R. 8 W., previously described.

Thence I run

West, on retracement of S. bdy. Sec. 33, following
plain traces of old survey line.

Descend steep ridge, in heavy timber and dense
undergrowth.

1.35 Spring branch, 1 lk. wide, course N., ascend.

16.70 Top of spur, bears N. and S., descend.

33.25 Creek, 2 lks. wide, course NW., ascend.

36.10 Top of ridge, bears N. and S., descend.

39.65 No trace of old $\frac{1}{2}$ sec. cor. to be found after
diligent search of old survey line.

43.30 Miners Creek, 2 lks. wide, course NE.

Ascend rocky ridge, 800 ft. high, almost insurmount-
able.

58.80 Top of rocky ridge, bears N. and S.

Old survey line, bears S., .92 chs. dist., plainly
marked.

Descend through heavy timber and dense undergrowth.