

County Surveyor's Record, Douglas County, Oregon

South Boundary of Township 24 S., Range 9 W., W. M., as surveyed by Wm. H. Byars, Deputy Surveyor under Contract 292, dated August 7, 1878.

CHAINS	Beginning at the SE cor. of Tp., I run West, on South boundary of Section 36. Va.18*E.
9.75	Lake, creek, 50 lks. wide, course, north.
40.00	Set cedar post, 4 feet long, 5 ins. dia., 18 ins. in ground for the $\frac{1}{4}$ Sec. corner on S. Bdy. of Sec.36, from which, Fir, 8 ins. dia., bears S.23*W., 30 lks. dist. Cedar,10 ins.dia., bears N.40*W., 21 lks. dist.
58.00	A Creek, 3 lks. wide, course N.
80.00	Set Fir post 40 ins. long 5 ins. dia., 20 ins. in ground for the corner to Secs. 35 & 36 on S. Bdy. from which a, Fir, 8 ins. dia., bears N.50*E., 11 lks. dist. Hemlock,10 ins. dia.,bearsS.33*E., 25 lks. dist. Fir, 36 ins. dia., bears S.21*W.,38 lks. dist. Fir, 30 ins. dia., bears N.70*W.,26 lks. dist.
	Land, hilly, 2nd rate. Timber, chiefly fir & cedar (good) underbrush same. Vine maple & hazel.
	West, on South boundary of Section 35. Va.18*E.
3.00	A creek, 5 lks. wide, course North.
12.25	A creek,10 lks. wide, course North.
40.00	Set a Laurel post, 3 feet long, 5 ins. dia., 18 ins. in ground for the $\frac{1}{4}$ Sec. corner on S. Bdy. of Sec. 35, from which a, Fir, 20 ins. dia., bears N.20*E., 13 lks. dist. Fir, 18 ins. dia., bears S.45*W., 4 lks. dist.
80.00	Set maple post 36 ins. long, 5 ins. dia., 18 ins. in ground for the corner to Sec. 34 & 35 on S. Bdy. from which a, Fir, 8 ins. dia., bears N.55*E., 27 lks. dist. Fir, 20 ins. dia., bears S.50*E., 38 lks. dist. Fir, 18 ins. dia., bears S.86*W., 75 lks. dist. Fir, 18 ins. dia., bears N.88*W., 26 lks. dist.
	Lands, hilly, 2nd rate. underbrush same. Vine, maple, huckleberry and hazel. Considerable down timber.