

Retracement of the East Boundary of T. 24 S., R. 10 W.

CHAINS	
3.30	The C. C. of secs. 18 & 19, T. 24 S., R. 9 W., bears East 1 lk. dist.
9.20	A stream, 6 lks. wide, 100 ft. below the cor. of secs. 13 and 24; course N. 70*W.
18.00	A branch, 3 lks. wide; course SW.
39.35	The $\frac{1}{4}$ sec. cor. bears E. 21 lks. dis. The old corner having been destroyed, I relocate the original cor. point by reference to the bearing trees where I set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for the $\frac{1}{4}$ sec. cor. marked. $\frac{1}{4}$ S 13 on W. face, witnessed as described by the Surveyor General. The true bearing of this line is therefore N.0*18'E. From $\frac{1}{4}$ sec. cor. Thence I run North, on a blank line. Ascend.
2.60	Main divide bet. Coos River and Lake Creek, 400 ft. above stream; bears E. and W. Descend 250 ft.
19.00	Cross a spur sloping NW. Descend 50 ft.
20.45	Foot of steep hill.
38.35	The cor. of secs. 12 and 13, bears East. 21 lks. dist. Which is a stone marked and witnessed as described by the Surveyor General. I obliterate all marks on the bearing trees referring to secs. 7 and 18. The true bearing of this line is therefore N.0*18'E. Land, mountainous. Soil, 3rd rate. Timber, fir, scattering chipquapin, laurel and hemlock. Undergrowth, rhododendron, vinemaple, salal and huckleberry. Land, mountainous, heavily timbered or covered with dense undergrowth 77.70 chs.

September 22, 1905