

Retracement of Subdivision of T. 24 S., R 9 W.

CHAINS

- 18.90 Top of a precipice, 100 ft. high.  
Set flag "A" on line and also flag "B" on line at foot of precipice.  
From B measure base West 1.00 chs. to C.  
(Owing to heavy timber longer base is impracticable.)  
From C, flag A bears S.17\*17'E.  
Cot.17\*17' = 3.21; therefore dist. from A to B = 3.21 chains.
- 22.11 Foot of precipice.
- 34.50 Branch, 2 lks. wide; course NE.
- 39.62 The  $\frac{1}{4}$  sec. cor which is a decayed post, marked and witnessed as described by the Surveyor General, bears West 87 lks. dist.  
The true bearing of this line is therefore N.1\*15'W.  
I destroy the old post and at the same point,  
Set a yew post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  S. on W., and 23 on E. face.  
Thence from the  $\frac{1}{4}$  sec. cor. I run North, on a blank line between secs. 22 and 23
- 1.00 Branch, 2 lks. wide; course NW.
- 2.75 Branch, 2 lks. wide; course NW.
- 7.60 Branch, 2 lks. wide; course W.
- 36.52 The post originally set for the cor. of secs. 14, 15, 22 and 23, bears west, 74 lks. dist.  
The true bearing of this line is therefore N.1\*10'W.
- 76.14 The old post being in a poor state of preservation, I destroy it and at the same point, set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 14 and 23 only, marked.  
T. 24 S S 14 on NE.  
R 9 W S 23 on SE. face, with 3 notches on S., and 2 notches on E. edge.

