

Retracement of Subdivisions of T. 24 S., R. 9 W

CHAINS

At the cor. of secs. 5 and 6.

Thence I run

S.89°45'W., on a blank line between secs. 6 and 7.

Over mountainous land, through heavy timber and dense undergrowth.

10.25 Falls in Lake Creek, bears South, 2.00 chains dis.

14.30 Lake creek, 75 lks. wide; course N.50°W.

23.00 Creek, 10 lks. wide; course North..

26.50 Point of spur slopes NE.

35.80 Bend in branch, 1 lk. wide; course SW.

39.78 The $\frac{1}{4}$ sec. cor., bears South, 93 lks. dis.

The cor. post is gone but the bearing trees remain as described by the Surveyor General.

In place of old post,

Set a maple post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S 6 on N. face; from which,

A fir, 8 ins. dia., bears S.34°E., 25 lks. dis.

mkd. as described by the Surveyor Gen.(old B. T.)

A hemlock, 12 ins. dia., bears N.20°W., 12 lks. dis.

mkd. as described by the Surveyor Gen.(old B. T.)

The true bearing of this line is therefore S.88°25'W.

From the $\frac{1}{4}$ sec. cor., I continue.

S.89°45'W., on a blank line.

3.25 Branch, 1 lk. wide; course NE. and ascend.

20.75 Ridge, 100 ft. above branch, bears N. and S. and descend.

31.00 Creek, 10 lks. wide, 75 ft. below ridge; course N. and ascend 150 ft. to.

37.28 Intersect West Bdy. of the township, 60 lks. south of the established cor. of secs. 1, 6, 7, and 12, which is a post marked and witnessed as described by the Surveyor General.