

Subdivisions of T. 24 S., R. 9 W.

CHAINS

At the cor. of secs. 8, 9, 16 and 17.

Thence I run

N.0*2'W., on a random line bet. secs. 8 and 9.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

71.06 Intersect E. and W. line, 2.56 chs. N.89*26'W. of the cor. of secs. 4, 5, 8 and 9, which is a post firmly set, marked and witnessed as described by the Surveyor General.

This close, being in excess of the prescribed limits, I retrace my line and finding no error therein, I return and destroy all marks on the old cor. and B.T's referring to Secs. 8 and 9, and at point of intersection of my random line with the S. line of sec. 5.

Set a hemlock post, 3 ft. long, 5 ins. sq., 24 ins. in the ground, for C. C. of secs. 8 and 9, marked

C C T 24 S R 9 W on S.,

S 9 on E., and

S 8 on W. face, with 5 grooves on S., and 4 grooves on E. face; from which

A fir, 36 ins. dia., bears S.29*E., 120 lks. dis. mkd. T 24 S R 9 W S 9 B T.

A fir, 48 ins. dia., bears S.77*W., 29 lks. dis. mkd. T 24 S R 9 W S 8 B T.

Thence I run

S.0*2'E., on a true line bet. secs. 8 and 9.

Descend over mountainous land through heavy timber and dense undergrowth.

1.16 Branch, 1 lk. wide, 70 ft. below C. C.; course NW.

12.76 Cross spur, sloping N.70*W., 100 ft. above branch.

25.01 A stream, 4 lks. wide, 180 ft. below spur; course NW. Ascend.

31.06 Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S 8 on W., and 9 on E face, from which