

Subdivision of T. 24 S., R 9 W.

CHAINS

the notes of W. H. Byers under contract No. 292, furnished by the Surveyor General.

This close being out of limits, both in measurement and alignment, I retrace my work and find it correct.

I then return to the cor. of secs. 25, 30, 31 and 36 and after destroying all marks on the old post and bearing trees referring to secs. 30 and 31, at the point of intersection,

Set a hemlock post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for C. C. of secs. 30 and 31,

mkd. C C T 24 S R 9 W on E.,

S 30 on N., and

S 31 on S. face, with 1 groove on S., and 5 grooves on N. face; from which

A fir, 24 ins. dia., bears N.20°E., 8 lks. dis.

mkd. T 24 S R 9 W S 30 B T.

A hemlock, 24 ins. dia., bears S.38°E., 23 lks. dis.

mkd. T 24 S R 9 W 31 B T.

At the cor. of secs. 25, 30, 31 and 36.

Thence I run

N.89°45'E., on a true line bet. secs. 30 and 31.

Over mountainous land through heavy timber and dense undergrowth.

16.74 Branch, 2 lks. wide, 50 ft. below sec. cor; course S.

25.00 Enter bench, bears N. and S.

34.00 Descend from bench.

35.24 Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ S 30 on N., and 31 on S. face; from which

A fir, 24 ins. dia., bears N.39°E., 20 lks. dis. mkd. $\frac{1}{4}$ S 30 B T.

A fir, 12 ins. dia., bears S.14°E., 82 lks. dis. mkd. $\frac{1}{4}$ S 31 B T.

September 9,