

Subdivision of T. 24 S. R. 9 W.

CHAINS

- C C T 24 S R 9 W on E.,
S 18 on N., and
S 19 on S. face, with 3 grooves on N. and S. faces;
from which
A fir, 8 ins. dia., bears N. $57\frac{1}{2}^{\circ}$ E., 57 lks. dis.
mkd. T 24 S R 9 W S 18 B T.
A fir 20 ins. dia., bears S. 69° E., 29 lks. dis.
mkd. T 24 S R 9 W S 19 B T.
- Thence I run
N. $89^{\circ}45'$ E., on a true line bet. secs. 18 and 19.
Over mountainous land through heavy timber and dense
undergrowth.
- 6.67 Branch, 1 lk. wide; course N.
12.00 Branch, 1 lk. wide; course N.W.
12.82 A stream, 6 lks. wide, 250 ft. below sec. cor; course
N. 70° W.
15.77 Branch, 1 lk. wide; course SW.
33.67 A blazed trail on main divide bet. Coos River and Lake
Creek, bears NW. and SE.
33.87 A fir tree, 26 ins. dia., for $\frac{1}{4}$ sec. cor., I mark $\frac{1}{4}$ S 18
on N., and 19 on S. face; from which
A fir, 24 ins. dia., bears S. 57° W., 54 lks. dis.
mkd. $\frac{1}{4}$ S 19 B T.
A fir, 30 ins. dia., bears N. 33° W., 18 lks. dis.
mkd. $\frac{1}{4}$ S 18 B T.
- Descend over small hills.
- 41.87 Head of gulch; course N.E.
48.87 Top of an ascent.
55.87 Top of spur, sloping SW., 100 ft. above stream at 12.82 chs.
60.37 Descend over rocky ledges.
63.87 Foot of rocky ledges, 100 ft. below spur.
Descend 200 ft.
73.87 The cor. of secs. 17, 18, 19 and 20.