

## County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 25 S., R 2 W., W.M.,  
as surveyed by John A. MoQuinn, D.S. Deputy Surveyor, under  
Contract No. 466 dated April 5, 1883.

## CHAINS

From the Cor. to Tps. 25 and 26 South Rgs. 1 and 2  
West, which is a post  $4\frac{1}{2}$  ft. long, 4 ins. square,  
firmly set in ground, marked

T 25 S S 31 on NE,

R 1 W S 6 on SE.,

T 26 S S 1 on SW., &

R 2 W S 36 on NW., faces with 6 notches on each edge  
from which

A Fir 30 in. dia. bears N.85\*E., 116 lks. dist.,  
marked T 25 S R 1 W S 31 B T.

A Pine 16 in. dia. bears N.55\*E., 45 lks. dist.,  
marked T 26 S R 1 W S 6 B T.

A Pine 16 in. dia., bears S.60\*W., 66 lks. dist.,  
marked T 26 S R 2 W S 1 B T.

A Fir 36 in. dia. bears N.68\*W., 138 lks. dist.,  
marked T 25 S R 2 W S 36 B T.

Thence I ran

North bet. secs., 31 and 36

Va.  $19\frac{1}{2}$ \*E.

13.40

A Fir 20 in. dia.,

38.50

Brook 6 lks. wide flows NE.,

40.00

Set post 3 ft. long, 3 ins., square, 24 ins., in  
ground for  $\frac{1}{4}$  Sec. Cor. marked  $\frac{1}{4}$  S. on W. face from  
which

A Fir 24 ins. dia., bears S.70\*E., 48 lks. dist.,  
marked  $\frac{1}{4}$  S B T.,

A Hemlock 24 ins. dia., bears N.41\*W., 17 lks. dist.,  
marked  $\frac{1}{4}$  S B T.,

41.50

Brook 3 lks. wide flows East.

42.50

Brook 3 lks. wide flows East.

57.50

Brook 4 lks. wide flows East.

58.30

A Hemlock 20 in. dia.

62.81

A Fir 36 in. dia.

80.00

Set post  $4\frac{1}{2}$  ft. long, 4 ins. square, 24 ins. in ground  
for Cor. to Secs. 25, 30, 31, & 36., marked