

County Surveyor's Record, ²Douglas County, Oregon

East Boundary of T. 25 S., R 2 W., W.M.,
as surveyed by John A. McQuinn, U.S. Deputy Surveyor, under
Contract No. 466 dated April 5, 1883.

CHAINS

T 25 S S 30 on NE.,
R 1 W S 31 on SE.,
R 2 W S 36 on SW., &
S 25 on NW., faces with 5 notches on N and 1 notch
on S Edges.

From which

A Fir 18 in. dia., bears N.40*E., 15 lks. dist.,
marked T 25 S R 1 W S 30 B T.,

A Fir 18 in. dia., bears S.44*E., 33 lks. dist.,
marked T 25 S R 1 W S 31 B T.,

A Fir 22 in. dia., bears S.28*W., 46 lks. dist.,
marked T 25 S R 2 W.S 36 B T.,

A Fir 12 in. dia., bears N.61*W., 16 lks. dist.,
marked T 25 S R 2 W S 25 B T.

Land mountainous.

Soil 3rd rate.

Densely covered with forests of fir, pine, hemlock,
maple, laurel and dogwood.

Thick undergrowth of laurel, hazel, vinemapple & sallah.

North bet. Secs., 25 and 30.

Va. 19 $\frac{1}{2}$ *E.

13.22	A Fir 36 in. dia.,	
14.00	A ridge bears NE.,	+500
18.00	Brook 4 lks. wide flows East.,	
27.10	A Hemlock 20 in. dia.	
40.00	Set post 3 ft. long, 3 ins. square, 24 ins. in ground for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S on W face	
	From which	
	A Sugar pine, 36 in. dia., bears West 42 lks. dist., marked $\frac{1}{4}$ S B T.,	
	A Laurel, 4 in. dia., bears S.20*E., 6 lks. dist., marked $\frac{1}{4}$ S B T.	
43.21	A Fir, 40 in. dia.	
80.00	Set post 4 $\frac{1}{2}$ ft. long, 4 ins. square, 24 ins. in ground	