

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 25 S., R 1 W., W.M.

CHAINS	
26.00	Creek, 1 lk. wide, 50 ft. below top of spur, course SW.
26.75	Creek, 3 lks. wide, course W., begin ascent.
33.50	Top of spur, 100 ft. above creek, begin descent. No diff., in measurements of 40.00 chs., by two sets of chainmen.
40.00	Set a madrone post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W face, from which A Fir, 24 ins. diam., bears S.50°E., 96 lks. dist., marked $\frac{1}{4}$ S B T. A Chinquapin, 6 ins. diam., bears S.35°W., 23 lks. dist., marked $\frac{1}{4}$ S B T. This cor. is on a hillside, sloping SW.
57.50	Creek, 6 lks. wide, course S.75°W., 75 ft. below top of spur, begin ascent. Va. 17°30'E.
60.75	Creek, 2 lks. wide, course W., continue ascent. Diff. bet. measurements of 80.00 chs. by two sets of chainmen, is 4 lks., position of middle point By 1st set, 80.02 chs., By 2nd set, 79.98 chs., the mean of which is
80.00	Set a fir post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for cor. of secs. 6, 7, 12 and 1, marked T 25 S S 6 on NE. R 1 E S 7 on SE. S 12 on SW., and R 1 W S 1 on NW., faces with 1 notch on N and 5 notches on S edges, From which A Fir, 16 ins. diam., bears N.26°E., 49 lks. dist., marked T 25 S R 1 E S 6 B T. A Fir, 48 ins. diam., bears S.54°E., 30 lks. dist., marked T 25 S R 1 E S 7 B T. A Fir, 60 ins. diam., bears S.48°W., 29 lks. dist., marked T 25 S R 1 W S 12 B T.