

County Surveyor's Record, Douglas County, Oregon

3483

East Boundary of T. 25 S., R 1 W., W.M.,
as surveyed by Carl S. Nicklin, U.S. Deputy Surveyor, under
Contract No. 664 dated May 23, 1896.

CHAINS

A Fir, 24 ins. diam., bears N.71*W., 4 lks. dist.,
marked T 25 S R 1 W S 1 B T.

This Cor. is on the summit of a mountain, 350 ft.

above creek noted at 57.50 chs., on this line, bet.,
secs., 1 and 6.

Land, mountainous.

Soil 3rd rate.

Timber, fir, Hemlock, cedar, yew, and chinquapin.

Land, mountainous, heavily timbered and covered with
dense undergrowth, 80.00 chs.

July 15:

At this sec. Cor., at 9 H. 30 M., A.M., l.m.t., I
set off 21*24'N., on declination arc, and 43*26'N.,
on lat. arc and determine a true meridian with the
solar.

Thence, I run

South, bet. secs., 7 and 12.

Va. 19*E.

Descend.

15.75 Pass over spur, sloping SW., continue to descend.

Va. 16*E.

30.75 Diff. bet., measurements of 40.00 chs., by two sets of
chainmen, is 6 lks., position of middle point

By 1st set, 40.03 chs.,

By 2nd set, 39.97 chs., the mean of which is

40.00 Set a basalt stone, 12x10x8 ins., 8 ins., in ground,
for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face from which

A Fir, 30 ins. diam., bears N.63*E., 18 lks. dist.,
marked $\frac{1}{4}$ S B T.,

A Fir, 12 ins. diam., bears N.49*W., 53 lks. dist.,
marked $\frac{1}{4}$ S B T.

This cor., is on a steep hill-side sloping W.

52.85 Creek, 4 lks. wide, 300 ft. below cor., of secs., 6,
7, 12 and 1, course S.10*E.

59.60 Same creek course S.10*W.