

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 25 S., R 1 W., W.M.,
as surveyed by Carl S. Nicklin, U.S. Deputy Surveyor, under
Contract No. 664 dated May 23, 1896.

CHAINS 63.40	<p>Same creek, course S.10°E.</p> <p>Gradually descend along hillside, sloping E.</p>
72.80	<p>Brink of inaccessible canyon.</p> <p>The sec. cor., would fall within the canyon.</p> <p>Therefore, at this point I</p> <p>Set a basalt stone, 16x12x8 ins., 12 ins., in the ground, for witness cor. of secs., 7, 12, 13 and 18, marked W C on NE face, with 2 notches on N and 4 notches on S edges, from which</p> <p>A Fir, 12 ins. diam., bears S.74°E., 16 lks. dist., marked W C., T 25 S R 1 E S 18 B T.,</p> <p>A Fir, 10 ins. diam., bears N.10°W., 45 lks. dist., marked W C., T 25 S R 1 W S 12 B T.</p> <p>No other bearing trees available.</p>
	<p>July 15.</p> <p>At this witness cor., I set off 21°22'N on the declination arc and observe the sun on the meridian at apparent noon, the resulting lat., is 43°25'N., which is about 32" greater than the proper lat.</p>
	<p>Thence,</p> <p>I off-set as follows:</p> <p>East, 2.25 chs., to creek, 10 lks. wide, course SW., thence east to off-set line, 5.83 chs. E., of witness cor., then I run South on off-set line.</p> <p>Ascend.</p>
78.11	<p>Top of ascent.</p> <p>Off-set line, W., 188 lks., then South on off-set line. Descend.</p>
79.53	<p>Off-set, W., 170 lks., then South on off-set line.</p>
80.00	<p>To point on off-set line, 2.25 chs., E. of point in canyon, where sec. cor., should fall.</p> <p>Land, mountainous.</p> <p>Soil, 3rd rate, and 4th rate.</p> <p>Timber, fir, hemlock, cedar, chinquapin, and madrona.</p> <p>Dense underbrush of rhododendron, vinemaple, hemlock, fir, cedar, chinquapin and sallal-berry.</p>