

County Surveyor's Record, Douglas County, Oregon

3485

East Boundary of T. 25 S., R 1 W., W.M.,
as surveyed by Carl S. Nicklin, U.S. Deputy Surveyor, under
Contract No. 664 dated May 23, 1896.

CHAINS

Land, mountainous, heavily timbered and covered with
dense undergrowth, 80.00 chs.

Note.-

The last 7 chs., of the last line, and the first
3 chs., of the next, consist of off-sets about
unscalable bluffs, which render it impossible to
set a sec. cor.

From a point 2.25 chs., E., of point where cor. of secs.,
7, 18, 13, and 12 should fall, I run South on offset
line.

2.42

Offset 2.25 chs. W., to meridian line.

On true line, set a basalt stone, 14x12x6 ins.,
10 ins., in the ground for witness cor. of secs.,
7, 12, 13 and 18, marked

W C on NE face, with 2 notches on N and 4
notches on S edges, from which

A Fir, 16 ins. diam., bears N.58°E., 20 lks.
dist., marked W C., T 25 S R 1 E S 7 B T.,

A Fir, 36 ins. diam., bears N.89°W., 20 lks. dist.
marked W C., T25 S R 1 W S 12 B T.

No other trees within limits.

This cor., is on a steep hillside sloping W.

Thence, South bet. secs., 13 and 18. Descent.

21.25

Creek, 4 lks. wide, 150 ft. below witness cor., course
W., continue descent.

Diff., bet., measurements of 40.00 chs., by two sets
of chainmen, is 22 lks., position of middle point

By 1st set, 40.11 chs.,

By 2nd set, 39.89 chs., the mean of which is

40.00

Set a basalt stone, 12x10x10 ins., 8 ins., in the
ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W face from
which

A Fir, 24 ins. diam., bears S.17°E., 19 lks. dist.,
marked $\frac{1}{4}$ SBT.